

Page: 1 of 7
Printed: 03/27/2020
Revision: 03/27/2020

Supersedes Revision: 02/03/2014

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: QS 155 2.8 | B

**Product Name:** Quik-Shield 155 2.8 I Resin (B)

Company Name: SWD URETHANE

539 S. Drew St. Mesa, AZ 85210,

Web site address: www.swdurethane.com

**Emergency Contact:** CHEMTREC

(800) 424-9300

#### 2. HAZARDS IDENTIFICATION

Acute Toxicity: Oral, Category 4
Acute Toxicity: Skin, Category 5

Serious Eye Damage/Eye Irritation, Category 2B



GHS Signal Word: Warning

GHS Hazard Phrases: H302 - Harmful if swallowed.

H313 - May be harmful in contact with skin.

H320 - Causes eye irritation.

GHS Precautionary Phrases: P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P273 - Avoid release to the environment.

GHS Response Phrases: GHS Storage and Disposal

Phrases:

Other Hazards: Causes mild skin irritation. Harmful to aquatic life.

Inhalation: May be harmful if inhaled. Causes respiratory tract irritation. May cause narcotic effects

in high concentration. Eye irritation, vertigo, and nausea were reported in humans

exposed at 2200 ppm.

**Skin Contact:** May be harmful if absorbed through the skin. Causes skin irritation. Causes moderate

skin irritation. May cause dermatitis.

Eye Contact: Causes eye irritation.

Ingestion: Harmful if swallowed. May cause gastrointestinal irritation with nausea, vomiting and

diarrhea. May cause central nervous system depression.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS # Ingredients/Components Concentration

77098-07-8 1,2-Benzenedicarboxylic acid, < 3.0 %

3,4,5,6-tetrabromo-, mixed esters with diethylene

glycol and propylen

NAHalogenated Phosphate7.0 -13.0 %NAProprietary Blowing Agent1.0 -3.0 %

111-76-2 Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, < 4.0 %

(a glycol ether)}

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 2 of 7 Printed: 03/27/2020 Revision: 03/27/2020

Supersedes Revision: 02/03/2014

#### 4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

In Case of Inhalation: If breathed in, move person into fresh air. If inhaled, remove to fresh air. If not breathing,

give artificial respiration. Get medical aid.

In Case of Skin Contact: Wash off with soap and plenty of water. Consult a physician. In case of contact, flush

skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if

irritation develops and persists. Wash clothing before reuse.

In Case of Eye Contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. In

case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get

medical aid.

**In Case of Ingestion:** Never give anything by mouth to an unconscious person. Rinse mouth with water.

Consult a physician. Get medical aid.

Signs and Symptoms Of

**Exposure:** 

To the best of our knowledge, the chemical, physical, and toxicological properties have

not been thoroughly investigated.

Note to Physician: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of

dangerous area. Treat symptomatically and supportively.

#### 5. FIRE FIGHTING MEASURES

Flash Pt:

Explosive Limits: LEL: UEL:

**Autoignition Pt:** 

Suitable Extinguishing Media: Use water spray, dry chemical, carbon dioxide, or alcohol-resistant foam.

Fire Fighting Instructions: Wear self contained breathing apparatus for fire fighting if necessary. As in any fire, wear

a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form explosive mixtures with air. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Fire or excessive heat may result in violent rupture of the container due to bulk polymerization. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors

can spread along the ground and collect in low or confined areas.

Flammable Properties and

Hazards:

**Hazardous Combustion** 

**Products:** 

## 6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or

Spilled:

Personal precautions.

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure

adequate ventilation.

Environmental precautions.

Do not let product enter drains.

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal. Use proper personal protective equipment as

indicated in Section 8.

Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place

in suitable container. Remove all sources of ignition. Use a spark-proof tool.

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 3 of 7 Printed: 03/27/2020 Revision: 03/27/2020

Supersedes Revision: 02/03/2014

#### 7. HANDLING AND STORAGE

Precautions To Be Taken in

Handling:

Avoid inhalation of vapor or mist.

Normal measures for preventive fire protection. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Avoid ingestion and inhalation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Pure vapor will be uninhibited and may

polymerize in vents or other confined spaces.

Precautions To Be Taken in

Storing:

Keep container tightly closed in a dry and well-ventilated place. Keep away from sources of ignition. Store in a tightly closed container. Flammables-area. Store protected from

light and air.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Partial Chemical Name OSHA TWA Other Limits** CAS# **ACGIH TWA** 77098-07-8 1,2-Benzenedicarboxylic acid, 3,4,5,6-tetrabromo-, mixed esters with diethylene glycol and propylen NA Halogenated Phosphate NA **Proprietary Blowing Agent** TLV: 200 ppm 111-76-2 PEL: 50 ppm TLV: 20 ppm

Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}

Respiratory Equipment (Specify Type):

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU). Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection: Face shield and safety glasses. Wear chemical splash goggles.

**Protective Gloves:** Handle with gloves. Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing: Choose body protection according to the amount and concentration of the dangerous

substance at the work place. Wear appropriate protective clothing to prevent skin

exposure.

**Engineering Controls** 

(Ventilation etc.):

Use process enclosure, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Facilities storing or utilizing this

material should be equipped with an eyewash facility and a safety shower.

Work/Hygienic/Maintenance

Practices:

Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 4 of 7 Printed: 03/27/2020 Revision: 03/27/2020

Supersedes Revision: 02/03/2014

			percedus 110 violetti. 02/00/2011				
9.	PHYSICAL AND CI	HEMICAL PROPERTIES	6				
Physical States:		[ ] Solid					
Appearance and Odor:	Viscous. Light. Brown.						
pH:							
Melting Point:							
Boiling Point:							
Flash Pt:							
Evaporation Rate:							
Flammability (solid, gas):							
Explosive Limits:	LEL:	UEL:					
Vapor Pressure (vs. Air or mm Hg):							
Vapor Density (vs. Air = 1):							
Specific Gravity (Water = 1):							
Solubility in Water:							
Octanol/Water Partition							
Coefficient:							
Autoignition Pt:							
Decomposition Temperature:							
Viscosity:							
10. STABILITY AND REACTIVITY							
Stability:	Unstable [ ] Stable [ X	(]					
Conditions To Avoid -	No data available.						
Instability:	Light, ignition sources, Exp						
Incompatibility - Materials To Avoid:	No dangerous reaction kno	wn under conditions of normal use	e. Strong bases, Copper.				
Hazardous Decomposition or	formed under fire condition	s. Carbon oxides,					
Byproducts:	Phosphorous oxides, Hydrogen chloride gas,						
	Thermal decomposition 244	4 °C Hydrogen chloride, phosgene	, Carbon monoxide.				
Possibility of Hazardous Reactions:	Will occur [ ] Will not o	occur [X]					
Conditions To Avoid -							
Hazardous Reactions:							



Page: 5 of 7 Printed: 03/27/2020 Revision: 03/27/2020

**OSHA** 

Supersedes Revision: 02/03/2014

11. TOXICOLOGICAL INFORMATION

**Toxicological Information:** Epidemiology: No data available.

Teratogenicity: No data available.

Reproductive Effects: Mutagenicity: Neurotoxicity: Other Studies:

CAS# NA:

Skin corrosion/irritation, Skin sensitization, This product does not contain any relevant quantities of materials with critical values that have to be monitored in the workplace.,

Rabbit, 0.000, Mild.

Results:

Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Eye: Lacrimation.

Behavioral: Tremor.

Lungs, Thorax, or Respiration: Cyanosis.

Irritation or Corrosion: Skin - rabbit - Mild skin irritation - 24 h.

> Serious eye damage/eye irritation: Eyes - rabbit - Mild eye irritation.

Carcinogenicity/Other

Carcinogenicity.

Information: IARC: No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is

identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. CAS# 156-60-5: Not listed

by ACGIH, IARC, NTP, or CA Prop 65.

CAS# Ingredients/Components NTP **IARC ACGIH** 

1,2-Benzenedicarboxylic acid, 3,4,5,6-tetrabromo-, mixed

esters with diethylene glycol and propylen

NA Halogenated Phosphate NA **Proprietary Blowing Agent** 

111-76-2 Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol 3 А3

ether)}

12. ECOLOGICAL INFORMATION

Persistence and

No data available.

Degradability:

77098-07-8

No data available. **Bioaccumulative Potential:** No data available. **Mobility in Soil:** 

13. DISPOSAL CONSIDERATIONS

Product. Waste Disposal Method:

Observe all federal, state, and local environmental regulations. Contact a licensed

professional waste disposal service to dispose of this material.

Contaminated packaging.

Dispose of as unused product. Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. RCRA P-Series: None listed.

RCRA U-Series:

CAS# 156-60-5: waste number U079.

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 6 of 7 Printed: 03/27/2020

Revision: 03/27/2020

Supersedes Revision: 02/03/2014

#### 14. TRANSPORT INFORMATION

GHS Classification: Acute Toxicity: Oral, Category 4 - Warning! Harmful if swallowed

Acute Toxicity: Skin, Category 5 - Warning! May be harmful in contact with skin Skin Corrosion/Irritation, Category 3 - Warning! Causes mild skin irritation Serious Eye Damage/Eye Irritation, Category 2B - Warning! Causes eye irritation

Aquatic Toxicity (Acute), Category 3 - Harmful to aquatic life

LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** Not Regulated.

DOT Hazard Class: UN/NA Number:

LAND TRANSPORT (Canadian TDG):

**TDG Shipping Name:** Not Regulated.

**UN Number:** 

Hazard Class: TDG Classification:

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Not Regulated.

UN Number: Packing Group:

**Hazard Class:** 

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Not Regulated.

(a glycol ether)}

UN Number: Packing Group:

**Hazard Class:** 

NA

#### 15. REGULATORY INFORMATION

ı	CAS#	Ingredients/Components	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)	
	77098-07-8	1,2-Benzenedicarboxylic acid,	No	No	No	
3,4,5,6-tetrabromo-, mixed esters with diethylene						
		glycol and propylen				
	NA	Halogenated Phosphate	No	No	No	
	NA	Proprietary Blowing Agent	No	No	No	
	111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether,	No	No	Yes-Cat. N230	

CAS # Ingredients/Components Other US EPA or State Lists

77098-07-8 1,2-Benzenedicarboxylic acid, CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - 3,4,5,6-tetrabromo-, mixed esters with diethylene Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA

glycol and propylen Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS:

No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No Halogenated Phosphate CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -

Inventory, 8D TERM; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No; PA HSL: No; SC TAP: No; WI

Air: No

NA Proprietary Blowing Agent CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA

PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No;

PA HSL: No; SC TAP: No; WI Air: No

111-76-2 Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -

(a glycol ether)} Inventory; CA PROP.65: No; CA TAC, Title 8: TAC: Cat. IIa,

Licensed to SWD Urethane: MIRS MSDS, (c) A V Systems, Inc.



Page: 7 of 7 Printed: 03/27/2020

Revision: 03/27/2020 Supersedes Revision: 02/03/2014

Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Yes - Cat.; NC TAP: Yes - Cat.; NJ EHS: Yes - Cat.; NY Part 597: No; PA

HSL: Yes - 1; SC TAP: Yes - Cat.; WI Air: Yes

CAS # Ingredients/Components International Regulatory Lists

77098-07-8 1,2-Benzenedicarboxylic acid, Canadian DSL: Yes; Canadian NDSL: No

3,4,5,6-tetrabromo-, mixed esters with diethylene

glycol and propylen

NA Halogenated Phosphate Canadian DSL: Yes; Canadian NDSL: No NA Proprietary Blowing Agent Canadian DSL: No; Canadian NDSL: No Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, Canadian DSL: Yes; Canadian NDSL: No

(a glycol ether)}

**Regulatory Information:** This product contains no chemicals subject to the reporting requirements of section 313

of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 40

CFR part 372.

Regulatory Information

Statement:

#### **16. OTHER INFORMATION**

**Revision Date:** 03/27/2020

**Additional Information About** 

This Product:

**Company Policy or** 

Disclaimer:

While the information and recommendations in this publication are given to the best of our knowledge, and information at the date of publication, nothing herein is to be construed as a warranty, expressed or otherwise. In all cases, it is the responsibility of the user to determine the applicability of such information, and recommendations or the suitability of any product for its own particular purpose.

The product may present hazards and should be used with caution. While certain hazards are described in this Safety Data Sheet, no guarantee is made that these are the only hazards that exist. Hazards, toxicity and behavior of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behavior should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED SWD EMPLOYEE SHALL PROVIDE, OR MAKE AVAILABLE, DATA SHEETS FOR SWD PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT THE WRITTEN PERMISSION OF SWD. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET OR QUESTIONS REGARDING THIS DATA SHEET SHOULD BE DIRECTRED TO SWD AT 800-828-1394.